

THREADED PLUGS AND BUSHINGS

Nominal Pipe Size	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
A	1 3/8	1 5/8	1 5/8	1 3/4	1 3/4	2	2	2	2 1/2	2 3/4	2 3/4	3
B	13/32	17/32	11/16	27/32	1 1/16	1 5/16	1 11/16	1 29/32	2 3/8	2 7/8	3 1/2	4-1/2
C*	7/16	5/8	11/16	7/8	1 1/16	1 7/16	1 13/16	2	2 1/2	3	3 3/4	4 5/8
D	1/4	1/4	5/16	5/16	3/8	3/8	9/16	5/8	11/16	3/4	13/16	1 1/4
E	7/16	1/2	9/16	11/16	3/4	27/32	7/8	15/16	1	1 1/4	1 9/16	1 21/32
F	9/32	3/8	7/16	9/16	5/8	13/16	15/16	1 1/8	1 5/16	1 1/2	1 11/16	2 1/2
G	1/4	1/4	5/16	3/8	7/16	1/2	9/16	5/8	11/16	3/4	13/16	1 1/4
H	3/8	7/16	1/2	9/16	5/8	3/4	13/16	13/16	7/8	1 1/16	1 1/8	1 3/8
J*		5/8	11/16	7/8	1 1/16	1 7/16	1 13/16	2	2 1/2	3	3 3/4	4 5/8
K		3/16	3/16	3/16	1/4	1/4	3/8	3/8	3/8	1/2	13/16	1 1/4
L		1/2	9/16	11/16	3/4	27/32	7/8	15/16	1	1 1/4	1 9/16	1 21/32
M		7/16	1/2	9/16	5/8	3/4	13/16	13/16	7/8	1 1/16	1 1/8	1 1/4
N	3/8	7/16	1/2	9/16	5/8	3/4	13/16	13/16	7/8	1 1/16	1 1/8	1 1/4

*Dimension J for Hex Head Bushing and dimension C for Hex Head Plug are the same.

Weights	1/8	1/4	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2	3	4
Round Head Plugs	0.125	0.125	0.188	0.25	0.375	0.75	1.125	1.563	3	4.75	7.62	12.87
Hexagon Plugs	0.063	0.063	0.125	0.188	0.313	0.5	1.125	1.375	2.25	3.87	5.87	13
Square Head Plugs	0.016	0.031	0.063	0.125	0.188	0.313	0.563	0.875	1.5	2.25	2.87	7.18
Hexagon Bushings		0.063	0.063	0.063	0.125	0.188	0.375	0.688	1.62	2.37	3.5	8.31
Flush Bushings		0.063	0.063	0.063	0.125	0.125	0.125	0.188	0.37	0.62	1	2



